

RELIANCE PROPERTY, B.C. 2020 - 2025 Drill Penetration Locations

Royal Shear Inclined Longitudinal Section

Elev. ASL (m)

1300

Section Looking NE at 066°
Parallels the Royal Shear Fault
Inclined at -58°

GOLD IN DRILLING (DDH & RC)

Gpt Gold x Metres (g x m)

- | | |
|---|---|
| ● 50 - 426 | ○ Assays Pending |
| ● 25 - 50 | VG Visible Gold |
| ● 10 - 25 | |
| ● < 10 | |

"The Company warns that the use of Gram x Metres is for visual presentation only on this longitudinal section. It is not meant to represent any metal accumulation or mineral resource tonnage."

"Gram x Metres is calculated by multiplying the composited gold grade (gpt) by the intersected drill length (m) of the reported assay composite. Gram x Metres is not a standard unit of measure and is non-compliant with NI 43-101 disclosure standards."

IMPERIAL

DDH25-120
1.81 Au / 7.0 m

CROWN GAP

VG
DDH25-119

DDH25-117
5.13 Au / 19.8 m
incl.
7.70 Au / 9.2 m

LOWER CROWN DISCOVERY

DDH25-121
10.15 Au / 1.5 m

DDH25-121
5.40 Au / 4.8 m
incl.
12.0 Au / 1.0 m

OPEN

OPEN

● OPEN

EAGLE

VG

OPEN

